



**Planetary Gear** with Straight Axle



**Digital Hour Meter** 



Finger Guard



Oil Jet for **Piston Cooling** 



Radiator with Overflow Reservoir



Top Shaft Lubrication



**Dry Type Air Filter** 



**Battery Inside Hood** 



Oil Immersed Disc Brakes

# John Deere **Genuine Parts**

I Economical I Reliable I Easily available I



## **TECHNICAL SPECIFICATIONS**

**ENGINE** 

Type : John Deere 3029D.

40 HP (29.8 kW),

2100 RPM, Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

**TRANSMISSION** 

Clutch : Single / Dual

: 8 Forward + 4 Reverse, Collarshift Gear box : Forward 2.84 - 31.70 kmph Speeds Reverse 3.74 - 13.52 kmph

#### **HYDRAULICS**

Maximum Lifting capacity: 1600 kgf 3 point linkage : Category - II

Automatic depth and draft control

(ADDC)

**POWER TAKE OFF** 

Type : Independent, 6 Splines Standard : 540 @ 2100 ERPM

WHEELS AND TYRES

Front : 8.0 X 18 (0.20 X 0.46 m), 8 PR : 13.6 X 28 (0.34 X 0.71 m), 12 PR Rear

**FUEL TANK** 

: 60 L Capacity

### **ACCESSORIES\***

- Ballast weights Canopy Canopy holder
- Draw bar Tow hook Wagon hitch

#### **FACTORY FITTED OPTIONS**

- Roll over protection structure (ROPS) with deluxe seat and seat belt
- Dual clutch

#### **FEATURES**

- PTO NSS Underhood exhaust muffler
- Water separator
- Front & Rear oil axle with metal face seal

# Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner

Long life and less maintenance

High torque reserve Ideal for heavy load applications

High torque across the operating speed range

#### 2WD model is also available

**Note:** 5 years warranty consist of 2 years / 2000 hours of standard warranty and extended warranty of 3 years / 3000 hours.

#### John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.









· Harvesters · Finance

