

Type

Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

TRANSMISSION

Clutch : Single / Dual

Gear box : 8 Forward + 4 Reverse, Collarshift Speeds : Forward 2.96 - 32.39 kmph

: Reverse 3.89 - 14.9 kmph

BRAKES

: Oil immersed disc brakes

HYDRAULICS

Maximum Lifting capacity: 1600 kgf 3 point linkage: Category - II

Automatic depth and draft control

(ADDC)

STEERING

Type : Power

POWER TAKE OFF

Type : Independent, 6 Splines Standard : 540 @ 2100 ERPM Economy : 540 @ 1600 ERPM

WHEELS AND TYRES

Front : 7.5 x 16 (0.19 x 0.41 m), 8 PR Rear : 14.9 x 28 (0.38 x 0.71 m), 12 PR

Note: 5 years warranty consist of 2 years / 2000 hours of standard warranty and extended warranty of 3 years / 3000 hours.

FUEL TANK

Capacity : 60 L

ELECTRICAL SYSTEM

: 88 Ah, 12 V battery, 40 Amp. Alternator,

12 V, 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight : 1870 kg
Wheel base : 1950 mm
Overall length : 3355 mm
Overall width : 1778 mm
Ground clearance : 0375 mm
Turning radius with brakes : 2900 mm

ACCESSORIES*

• Ballast weights • Canopy • Canopy holder

• Draw bar • Tow hook • Wagon hitch

FACTORY FITTED OPTIONS

Reverse PTO • Dual PTO

 Roll over protection structure (ROPS) with deluxe seat and seat belt

· Adjustable front axle

• Mechanical quick raise and lower (MQRL)

Selective control valve (SCV)

FEATURES

• Collarshift type gear box • PTO NSS • Water separator

• Digital hour meter • Mobile charging point with holder

Planetary gear with straight axle • Finger guard

Hydraulic auxiliary pipe
 Underhood exhaust muffler

Note: All the options / features may not be available in a single variant.

4WD model is also available

NEW 5205 48HP 35.1 kW

Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner
 Long life and less maintenance

High torque reserve
 Ideal for heavy load applications

High torque across the operating speed range

Rear oiled axle with metal face seal



Dry Type Air Filter



Oil Jet for Piston Cooling



Radiator with Overflow Reservoir



Top Shaft Lubrication


John Deere Genuine Parts

I Economical I Reliable I Easily available I



John Deere India Private Limited


3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in











Harvesters • Finance

