







Mobile Charging Point with Holder



Hood Lock



Planetary Gear with Straight Axle





Technical Specifications

ENGINE	
Туре	 John Deere 3029D, 45 HP (33.5 kW), 2100 RPM, 3 Cylinders, Coolant cooled with overflow reservoir, Naturally aspirated
Air filter	: Dry type, Dual element

TRANSMISSION

Clutch : Dual
Gear box : 8 Forward + 4 Reverse, Collarshift
Speeds : Forward 2.83 - 30.92 kmph
Reverse 3.71 - 13.43 kmph

BRAKES

HYDRAULICS

Maximum Lifting capacity : 1600 kgf 3 point linkage : Category - II

Automatic depth and draft control

: Oil immersed disc brakes

(ADDC)

STEERING

Type : Power

POWER TAKE OFF

Type : Independent, 6 Splines Standard : 540 @ 2100 ERPM Economy : 540 @ 1600 ERPM

WHEELS AND TYRES

Front : 8.0 X 18 (0.20 x 0.46 m), 8 PR Rear : 13.6 X 28 (0.34 x 0.71 m),

12 PR (Standard)

: 14.9 X 28 (0.38 x 0.71 m),

12 PR (Optional)

FUEL TANK

Capacity : 60 L

ELECTRICAL SYSTEM

: 88 Ah, 12 V battery, 40 Amp. alternator, 12 V, 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight : 1975 kg
Wheel base : 1950 mm
Overall length : 3370 mm
Overall width : 1810 mm
Ground clearance : 0360 mm
Turning radius with brakes : 2900 mm

ACCESSORIES*

- Ballast weights Canopy Canopy holder
- Draw bar Tow hook Wagon hitch

FACTORY FITTED OPTIONS

- Jolink (Alerts, Monitoring and Tracking System)
- Reverse PTO
- Roll over protection structure (ROPS) with deluxe seat and seat belt
- Mechanical quick raise and lower (MQRL)
- Selective control valve (SCV) Dual PTO



FEATURES

- Collarshift type gear box Finger guard PTO NSS
- Underhood exhaust muffler Water separator
- Single piece hood opening with gas struts

2WD model is also available

Note: All the options / features may not be available in a single variant.

Note: 5 years warranty consist of 2 years / 2000 hours of standard warranty and extended warranty of 3 years / 3000 hours.

New 45 HP 4WD Model 5045 D

Modern, technologically advanced, powerful John Deere 3029D engine

- Wet liner
 Long life and less maintenance
- High torque reserve
 Ideal for heavy load applications
- High torque across the operating speed range



Dry Type Air Filter



Oil Jet for Piston Cooling



Radiator with Overflow Reservoir



Top Shaft Lubrication

John Deere Genuine Parts

I Economical I Reliable I Easily available I




For more information, please contact our authorised dealer or nearest area office.

John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

Please note: Improvement in the product is a continuous process Hence the information given in this brochure is subject to change without prior notice. Accessories shown are not the part of standard equipment.



• Harvesters • Finance

