





Technical Specifications

Model	SD1009	SD1013
Number of Tines	9	13
Suitable Tractor Models	5036 C, 5041 C, 5038 D,	5050 D, 5050 E,
	5042 D, 5045 D, 5045 D 4WD	5055 E, 5055 E 4WD, 5060 E
Seed/Fertilizer Capacity, Kg	65 / 60	120 / 115
Soil Opener	Shovel	
Seed and Fertilizer Metering	Fluted Roller Type Metering	
Overall Width, mm	2030	2600
Operating Width, mm	1800	2375
Depth of Operation, mm	40 to 60	

CAT II, 3 Point Hitch Geometry.

Optional Accessory: Side disc assembly to create bund for irrigation.

Salient Features



Seed and Fertilizer **Rate Adjustment** Mechanism

Makes implement suitable for different seed rates and sizes.

Spiked Ground Wheel

Spiked wheel makes it

suitable for working in

sticky soil.



Transparent Tubes for Seeds and Fertilizers

- · Transparency allows easy inspection.
- The plastic cap enables effortless attachment and detachment of fertilizer tubes, making it easy to wash in case of clogging.



Adjustable Row to Row Spacing

Makes implement suitable for a variety of crops and row spacing requirements.



Adjustable Marker

Helps to maintain uniform row to row spacing.



Depth Adjusting Wheel

Makes the implement suitable for sowing variety of crops in different field conditions.








Rust-free Seed & Fertilizer Metering System

Use of aluminium and nylon parts make the metering system corrosion-resistant, thus increasing longevity.



John Deere India Private Limited

Sanaswadi, Pune-Nagar Road, Pune - 412208 www.JohnDeere.co.in









